

Gestetner

Digital B&W MFP

MP 2001SP/2501SP



Konfigurasi Standar MP 2001SP



Konfigurasi Standar MP 2501SP

Color Touchscreen

Layar-sentuh 4.3" memberikan akses yang mudah & cepat pada fitur2 yang tersedia. Panel tampilan dapat diatur kemiringannya dengan tampilan fungsi icon2 Sphere yang dapat di-program sesuai kebutuhan masing2 pengguna

Color Scanner

Fasilitas scan warna meningkatkan kebutuhan proses dokumen. Melalui Scan kirim langsung ke alamat email, folder & USB yang dilengkapi dengan format PDF-A, memenuhi standar sistem ke-arsipan dokumen secara elektronik.

Eco-Friendly MFPs

Dilengkapi dengan fitur2 ramah lingkungan yang menghemat pemakaian kertas, bahan pakai & konsumsi listrik (Energy Star Compliance).



Gestetner MP 2001SP/2501SP

GENERAL

Warm-up time	: 20/20 second
First output speed	: 6/6 seconds
Continuous output speed	: 20/25 pages per minute
Memory	: Standard : 1 GB maximum : 1.5 GB
HDD	: Option : 250 GB
Dimensions (W x D x H)	: 587 x 568 x 460/587 x 568 x 558 mm
Weight	: 38/44 kg
Power source	: 220-240 V, 50/60 Hz
Max paper Size	: 305 x 600 mm

COPIER

Copying process	: Laser beam scanning and electro- photographic printing
Multiple copying	: Up. To 999 copies
Resolution	: 600 dpi
Zoom	: From 50% to 200%

PRINTER

Printer language	: Standard : PCL5e, PCL6, PDF Option : Adobe® PostScript® 3™
Print resolution	: 600 x 600 dpi
Interface	: Standard : USB 2.0, SD slot, USB Host I/F, Ethernet 10 base-T/100 base-TX, Ethernet 1000 Base-T Option : Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g) Bluetooth
Network protocol	: TCP/IP (IP v4, IP v6), IPX/SPX
Windows environments	: Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® server 2008, Windows® Server 2008R2
Mac OS Environments	: Macintosh OS X v10.5 or later
UNIX Enviroments	: UNIX Sun® Solaris : 2.6, 2.7, 2.8, 2.9, 2.10 HP-UX : 10.x, 11.x, 11i v2, 11i v3, SCO OpenServer : 5.0.6, 5.0.7, 6.0 RedHat® Linux Enterprise: 4, 5, 6 IBM® AIX: 5L v5.3, 5L v6.1, 5L v7.1 IBM® System i5™ HPT
Novell Netware Environments	: v6.5
SAP R/3 enviroments	: SAP® R/3.x or later mySAP ERP 2004 or later
Citrix enviroments	: Citrix Presentation Server 4.0, 4.5 Xen App 5.6, 6.0, 6.5

SCANNER

Scanning speed	: Full Colour : Maximum 50 originals per minute B/W : Maximum 50 Originals per minute
Resolution	: Maximum : 600 dpi, 1200 dpi (TWAIN)
Original size	: A3, A4, A5
File format	: TIFF, JPEG, PDF, Encrypt PDF High compression PDF
Bundled drivers	: Network TWAIN, Scanner utility
Scan to	: E-mail, Folder, USB/SD, URL, WSD Scanner

PAPER HANDLING

Recommended paper size	: Paper tray(s): A5 - A3 Bypass tray: A6 - 305 x 600 mm
Paper input capacity	: Standard : 350/600 sheets Maximum : 1,350/1,600 sheets
Paper output capacity	: Standard : 250 sheets Maximum : 350 sheets
Paper weight	: Standard paper tray(s) : 60-105 g/m ² Bypass tray: : 60-162 g/m ² Duplex : 64-90 g/m ²

ECOLOGY

Power consumption	: Maximum: 1.55 kw Ready mode : 113W Printing +/- 450W Sleep mode : 0.6W TEC (Typical Electricity Consumption) : 892/1,082 W/h
-------------------	--

SOFTWARE

Standard	: Smart Device Monitor, Web Smart Device Monitor® Web Image Monitor
Optional	: Didac (Digital Data Conversion) eDocGSM Season II

OPTIONS

ADF handle, Platen cover, ARDF, 1 x 500-sheet paper tray, 2 x 500-sheet paper tray,
One-bin tray, Hard disk drive, RAM, VM card, Netware, Browser unit, Adobe®
PostScript® 3™ option, Counter Interface, File format converter, Copy data security.

For availability of models, options and software, please consult to PT Setiawan Sedjati.

