RICOH
imagine. change.

Perangkat Multi Fungsi kelas Produksi Hitam Putih

Ricoh Pro 8300s

☑ Copier ☑ Printer ☑ Scanner

Pro 8300s
96 ppm
Hitam Putih

RICOH

The Power of Black & White

Perangkat Multi Fungsi kelas Produksi Hitam Putih yang berkualitas tinggi, kini hadir dengan kemampuan yang luar biasa, lebih handal dan dapat menangani produksi cetak volume besar

Ricoh seri Pro 8300s menggunakan Teknologi VCSEL 40ch, menghasilkan resolusi s/d 2.400 x 4.800 dpi - terbaik dikelasnya. Hasil cetak yang konsisten baik untuk kualitas hitam putih maupun kepresisian dari setiap lembarnya untuk volume besar.

Ricoh seri Pro 8300s dapat mencetak pada media dengan ukuran maksimal 330 x 700* mm dan berat media 40 - 350* gsm. Dapat mencetak pada berbagai jenis media, spt : Coated Paper, Amplop, NCR, kertas tekstur, stiker, dll. Dllengkapi dengan Paper Library sehingga pengolahan media cetak dapat diatur dgn mudah dan cepat sesuai kebutuhan.

Ricoh seri Pro 8300s hadir dengan kecepatan cetak mulai dari 96 ppm. Pro seri 8300s juga merupakan perangkat cetak kelas "Heavy-duty". Kapasitas penampung kertas s/d 12.600 lembar dan didukung dengan 2 slot toner secara bergantian sehingga proses cetak dapat tetap berjalan tanpa gangguan.

Konfigurasi Ricoh Pro 8300s*

Konfigurasi Mesin & Aksesoris disesuaikan dgn kebutuhan

1 Shift Sort Tray SH5000

Baki penampung keluaran kertas yg dapat menampung s/d 1.250 lembar

Ukuran Mesin : 399 x 599 x 480 mm
Berat Mesin : 11 kg

LCIT RT5120 Vaccum Feed

Baki penampung kertas dengan sistem vakum dengan kemampuan kapasitas 4.400 lembar (2 x 2.200 lembar)

Ukuran Kertas : Min. = 140 x 216 mm
Maks. = 330 x 487 mm
Berat Kertas : 40 - 350 gsm
Daya Listrik : dibawah 860 Watt
Ukuran Mesin : 1.054 x 729 x 1.001 mm
Berat Mesin : 230 kg

Staples Finisher SR5090

Finisher penampung hasil cetak yg otomatis staples s/d 65 lembar / 130 halaman.

Kap. Kertas : maks. = 3.000 lembar
Ukuran Kertas : 100 x 140 - 330 x 487 mm
Berat Kerta : 40 - 350 gsm
Posisi Staples : atas, atas miring dan 2 dipinggir
Ukuran Mesin : 658x 730 x 980 mm
Berat Mesin : 38 kg

Multi Folding Unit FD5020

Unit pelengkap Finisher yg berfungsi sebagai pelipat hasil cetak.

Model Pelipatan : Half Fold, Z Fold, Double Parallel Fold, Gate Fold, dll.
Ukuran Kertas : 210 x 280 - 330 x 487 mm
Ukuran Mesin : 470 x 730 x 1.000 mm
Berat Mesin : 92 kg

2 LCIT RT5110

Baki penampung masukan kertas dengan kapasitas 4.400 lembar (3 baki).

Kap. Kertas : Baki 4 & 6 = 1.100 lembar
Baki 5 = 2.200 lembar
Ukuran Kertas : 100 x 140 - 330 x 487 mm
Berat Kerta : 40 - 300 gsm
Ukuran Mesin : 865 x 730 x 1.000 mm
Berat Mesin : 185 kg

3 Booklet Finisher SR5100

Finisher penampung hasil cetak yang otomatis bisa staples booklet (staples tengah) maks. 20 lembar / 80 halaman dan juga bisa staples pinggir maks. 65 lembar / 130 halaman.

Kapasitas Kertas : maks. 2.000 lembar
Ukuran Kertas : 216 x 279 - 330 x 457 mm
Berat Kertas : 40 - 350 gsm
Posisi Staples : Atas, 2 disamping, atas miring, 2 ditengah
Ukuran Mesin : 358 x 730 x 980 mm
Berat Mesin : 58 kg

Perangkat Controller

EFI Fiery EB-35

Server EFI yang bermanfaat untuk mengatur proses cetak menjadi mudah dan cepat.

CPU : Intel Processor G4400, 3.3 GHz
RAM & HDD : 8 GB & 500 GB
System : FS 300 Pro

RICOH

RICOH Pro 8300s

SPESIFIKASI SISTEM

RICOH @Remote

Spesifikasi Mesin

Model Mesin	Pro 8300s – Copy/Print/Scan
Proses Print / Copy	Sistem perpindahan toner menggunakan transfer belt
Sistem Pemanas	Metode pemanas dengan belt
Registrasi Kertas	Sensor dan Mekanik
Layar Panel Operasi	Layar sentuh 17" berbasis Android
Kecepatan Cetak	96 lembar per menit
Kecepatan Awal Cetak	6,3 detik
Maks. Cetak/Bulan	1.000.000 lembar
Resolusi	VCSEL : 2400 x 4800 dpi Print : 1200 x 1200 dpi
Kapasitas Kertas	Baki 1 : 1.100 x 2 Baki 2 & 3 : 550 x 2
Ukuran Kertas	Baki 1 : 216 x 279 mm Baki 2 & 3 : 140 x 216 mm - 330 x 457 mm
Berat Kertas	Baki1-3 : 52 - 256 gsm
Tipe Kertas	Plain, Recycled, Colored, Letterhead, Preprinted, Pre-punched, Bond, Card, OHP*, Tab*, Transparency*, Label*, Gloss*, Matte*, Envelope*
Kebutuhan Listrik	208-240 V, 50/60 Hz, 20A
Konsumsi Listrik	12.1 kWh/minggu
Konsumsi Listrik Maks.	Kurang dari 2800 Watt
Waktu Tunggu	Kurang dari 300 detik
Ukuran (PxLxT)	1.141 x 900 x 1.558 mm tanpa lampu indikator 1.141 x 900 x 1.735 mm dengan lampu indikator
Berat	428 kg
ENERGY STAR EPEAT	Tersertifikasi kelas Emas

Fitur Copy

Duplex Copying, Simplified Display, Auto Paper Selection, Auto Reduce/Enlarge, Auto Start, Auto Tray Switching, Auto Image Density, User Codes (1,000), Job Programs (50), Image Rotation, Interrupt Copy, Job Presets, Book/Series/Combine Copying, Cover/Chapter/Slip Sheet, Tabs, Sample Copy, Stamps/Numbering, Bates Numbering, Shift/Erase/Margin Adjustment, Customizable Home Screen, Eco-Friendly Indicator, Energy Saver, Weekly Timer, External USB Keyboard Support, Web Browser, Copy Reservation (10), A3/DLT Counter, Mixed Sizes, Batch Mode

Fitur Keamanan

Data Encryption (Address Book, Authentication Password, SSL Communication, S/MIME, IPsec Communication, HDD), User Authentication (Windows*, LDAP, Basic, User Code, 802.1.x Wired), Network Protocol On/Off, IP Filtering, Unauthorized Copy/Print Control, SMTP over SSL, Mandatory Security Information Print (Compulsory Security Stamp)

Spesifikasi Printer

Konfigurasi	Tertanam
CPU	Intel® Atom® Processor BayTrail – 1.91 GHz
RAM	2 GB
HDD	640 GB
Koneksi Antarmuka	Ethernet (1000BASE-T/100BASE-TX/10Base-T), USB 2.0 Type A (2 ports on Controller board and 4 ports on operation panel) USB 2.0 Type B (1 port on Controller board), SD slot (1 on operation panel)
Koneksi Tambahan	IEEE802.11a/b/g/n, Bluetooth
Koneksi Jaringan	TCP/IP (IPv4, IPv6)

Sistem Operasi
Windows 7/8.1/10/Server 2008/Server 2008R2/Server 2012/Server 2012R2/Server 2016/Server 2019; Mac OS x 10.11 or later; NetWare 6.5, UNIX Sun Solaris 10, HP-UX 11.x/11i v2/11i v3, SCO OpenServer 5.0.7/6.0, RedHat Linux Enterprise V4/V5/V6, IBM AIX V6.1/V7.1/V7.2, SAP R/3, S/4

Print Drivers	Standard: PCL5c, PCL6 (XL), PDF Optional: Adobe PS3, Genuine
PDL	IPDS PCL 5e, PCL 6, PDF, JPEG,
Optional PDL	TIFF Adobe PostScript 3, IPDS
Fonts	PCL: 45 fonts + 13 international

Fitur Printer

Send to Document Server, Sample/Locked/Hold/Stored/Scheduled Print, Store and Print, Layout (N-up), Banner Page Print, PDF Direct Print, Mail to Print, Classification Code, Bonjour Support, Windows Active Directory Support, DDNS Support, PCL Resident Font Adoption, Tray Parameter Change from Web Image Monitor, 1200 dpi Support, WSD Print, Media Direct Print (Print from USB/SD), Auto Job Promotion, Poster Print

Spesifikasi Scanner

Penarik Original	220 lembar ADF dgn 1x scan membaca 2 gambar warna sekaligus
Resolusi Scan	100/150/200/300/400/600 dpi
Area Scan	s/d 297 x 432 mm
Kecepatan Scan	1 sisi : 120 ipm; 2 sisi : 220 ipm (hitam putih dan warna)
Format Hasil Scan	Satu Halaman : TIFF/JPEG/PDF/ High Compression PDF; Banyak Halaman : TIFF/JPEG/PDF/ High Compression PDF
Penghubung Jaringan	Ethernet (1000BASE-T/100BASE-TX/10Base-T),USB2.0 Type A, SD card slot
Authentication	SMTP/POP before SMTP

Fitur Scanner

Scan to USB/SD, Scan-to Email/Folder/SMB/FTP/URL/PDF/A, Searchable PDF (OCR Option Required), WSD Scanner, TWAIN Scanning, Scanned File Naming, LDAP Support, Distributed Scan Management, Preview Before Transmission, PDF Encryption, Drop Out Color Send, Auto Color Selection, Auto Density, Auto Size Detection, Image Rotation, Mixed Size/SADF/Batch Mode, Reduce and Enlarge, Split Scan, JBIG2 Compression Support

Spesifikasi Document Server

Penyimpanan Dokumen Maks.	: 3.000
Jumlah Halaman Maks. per Dokumen	: 15.000

Aksesoris

TK5020 A3/DLT Tray Unit (Option for Main Unit Tray 1)

Kapasitas Kertas	1.000 lembar
Ukuran Kertas	216 x 279 mm, 216 x 355 mm, 279 x 431 mm

LCIT RT5130 A4/LT Large Capacity Input Tray

Kapasitas Kertas	5.000 lembar Baki 4 : 1.100 lembar Baki 5 : 1.100 lembar Baki 6 : 2.800 lembar
Ukuran Kertas	140 x 216 mm - 216 x 279 mm
Berat Kertas	Baki 4 - 5 : 52 - 216 gsm Baki 6 : 52 - 163 gsm
Ukuran (P x L x T)	540 x 730 x 1.000 mm
Berat	**106 kg**

LCIT RT5110 A3/DLT Large Capacity Input Tray

Kapasitas Kertas	4.400 lembar Baki 4 : 1.100 lembar Baki 5 : 2.200 lembar Baki 6 : 1.100 lembar
Ukuran Kertas	100 x 140 mm - 330 x 487 mm
Berat Kertas	Baki 4 & 6 : 52 - 256 gsm Baki 5 : 40 - 300 gsm
Sistem Udara/Angin	Mendukung di semua Baki
Ukuran (P x L x T)	865 x 730 x 1.000 mm
Berat	185 kg

BY5020 Multi Bypass Tray

Kapasitas Kertas	500 lembar
Ukuran Kertas	100 x 140 mm - 330 x 487 mm
Berat Kertas	52 - 216 gsm

SR5090 3,000-Sheet Finisher with 65-Sheet Stapler

Shift Tray

Kapasitas Kertas	3.000 lembar (216 x 279 mm (LEF)) 1.500 lembar (216 x 279 mm (SEF) 216 x 355 mm - 279 x 431 mm)
Berat Kertas	40 - 350 gsm

Baki Keluaran Atas

Kapasitas Kertas	250 lembar (dibawah 216 x 279 mm) 50 lembar (diatas 216 x 355 mm)
Berat Kertas	52 - 216 gsm
Ukuran Kertas	100 x 140 mm - 330 x 487 mm
Pelubangan	2/3 lubang (aksesoris tambahan)
Staples	2 - 65 lembar
Berat Kertas Staples	s/d 105 gsm
Posisi Staples	Top, Bottom, 2 Staples, Top Slant
Ukuran (P x L x T)	658 x 730 x 980 mm
Berat	38 kg

SR5100 2,000-Sheet Booklet Finisher with 65-Sheet Stapler

Shift Tray

Kapasitas Kertas	2.000 lembar (216 x 279 mm (LEF)) 1.500 lembar (216 x 279 mm (SEF) 216 x 355 mm - 279 x 431 mm)
Berat Kertas	40 - 350 gsm

Baki Keluaran Atas

Kapasitas Kertas	250 lembar (dibawah 216 x 279 mm) 50 lembar (diatas 216 x 355 mm)
Berat Kertas	52 - 216 gsm
Pelubangan	2/3 lubang (aksesoris tambahan)
Staples	
Ukuran Kertas	2 - 65 lembar
Berat Kertas	s/d 105 gsm
Posisi Staples	Top, Bottom, 2 Staples, Top Slant

Staples Booklet

Ukuran Kertas	216 x 279 mm - 330 x 457 mm
Berat Kertas	64 - 80 gsm - s/d 20 lembar
Posisi	2 dibagian tengah
Ukuran (P x L x T)	358 x 730 x 980 mm
Berat	58 kg

SH5000 Shift Sort Tray

Kapasitas Kertas	1.250 lembar (216 x 279 mm) 500 lembar (216 x 355 mm - 304 x 457 mm)
Berat Kertas	52 - 216 gsm
Ukuran (P x L x T)	400 x 600 x 480 mm
Berat	11 kg

Aksesoris Tambahan

Attention Light AL3000, Punch Unit PU3090 NA, Output Jogger Unit Type M25, Decurl Unit DU5070, ADF Double-feed Detection Kit Type S7, Media Identification Unit Type S3, TCRU/ORU Type S11 (Set A), ORU Type S11 (Set B), PostScript3 Unit Type S11, IPDS Unit Type S11, NFC Card Reader Type S6, Optional Counter Interface Unit Type M12, IEEE802.11a/b/g/n, OCR Unit Type M13, VM Card Type P18, File Format Converter Type M18, EFI Printer Controller EB-35, Vacuum Feed LCIT RT5120, Bridge Unit BU5010, Vacuum Feed Banner Sheet Tray Type S9, Multi Bypass Attachment Kit for Vacuum Feed LCIT Type S9, Multi Bypass Banner Sheet Tray Type S9, SR5000 series Output Tray for Banner Sheet Type S6, Multi-Folding Unit FD5020, Finisher SR5110, Booklet Finisher SR5120, Punch Unit PU5030 NA, Trimmer Unit TR5050, Cover Interposer Tray CI5040, Cover Interposer Tray Double-Feed Detection Kit Type S11

Kapasitas Bahan Pakai

Toner : 82.000 cetakan per botol*

***Berdasarkan Coverage 6% dalam kondisi mesin normal**

Untuk hasil yang maksimal di WAJIB kan menggunakan Spare Part dan Bahan Pakai asli dari PT. Setiawan Sedjati.

Exclusive Distributor :

PT. SETIAWAN SEDJATI

Mugi Griya Building 8th Floor
Jl. M.T. Haryono Kav.10
Jakarta 12810, Indonesia
Telp. : (021) 8308521 - 27
Fax. : (021) 8308529
www.setiawansedjati.com

Branch Office & Stations :
* Medan * Banda Aceh * Lhokseumawe * Pematang Siantar * Padang * Pekanbaru * Palembang * Jambi * Bandar Lampung * Pangkal Pinang * Jakarta 1 * Jakarta 2 * Jakarta 3 * Banten * Bogor * Bekasi * Bandung * Cirebon * Tasikmalaya * Sukabumi * Karawang * Semarang * Tegal * Pekalongan * Yogyakarta * Solo * Purwokerto * Magelang * Surabaya * Malang * Jember * Banjarmasin * Balikpapan* Pontianak * Denpasar * Mataram * Kupang * Maumere * Makassar * Manado * Palu * Palopo * Kendari * Sorong * Ambon * Manokwari * Jayapura * Merauke