

Perangkat Cetak Digital Produksi Warna

RICOH Pro™ C7500

✓ Printer

RICOH
imagine. change.



**Kreativitas tanpa batas
dengan Warna ke-5**

**RICOH Pro
C7500***

95
ppm
Hitam Putih
Warna

**RICOH Pro
C7500**

85
ppm
Hitam Putih
Warna

* dengan Opsi Productivity Upgrade

RICOH

The Next Level of Color

*Kembangkan bisnis produksi cetak warna dengan “**INOVASI TANPA BATAS**” melalui **RICOH Pro C7500**.*

Ricoh Pro C7500 dapat mencetak pada media s/d 330 x 1.260 mm (Simplex) dan 330 x 960 mm (duplex) dengan berat media mulai dari 40 - 470 gsm.

Hadirnya warna ke-5 khususnya Neon Yellow dan Neon Pink akan memperluas gamut warna - gabungan warna CMYK + Neon Yellow/Neon Pink. Begitu juga dengan Toner Silver dan Gold akan membentuk warna metalik yang menarik dan atraktif.



Tersedia pilihan warna ke-5 : White, Clear, Neon Pink, Neon Yellow, Invisible Red, Silver dan Gold

Konfigurasi Ricoh Pro C7500*



**Main Unit Pro C7500 + Vacuum Feed
LCIT RT5150 + Extension Vacuum
Feed Banner Sheet Tray Type S14 +
Finisher SR5110 + Extension Output
Banner Sheet Tray Type S14 +
Color Controller N-50A + ES-3000**

*** Konfigurasi Mesin sesuai kebutuhan**

Pilihan Aksesoris

Vacuum Feed LCIT RT5150



Baki penampung kertas dgn sistem vakum (seperti offset)

- Bisa dipasang s/d 3 unit dalam 1 mesin
- Maks. Ukuran Kertas = 330 x 487 mm
- Berat = 230 kg
- Kapasitas baki = 4.400 lembar (2.200 x 2 baki)
- Maks. Berat Kertas = 470 gsm

Multi Bypass Tray BY5020 + Multi Bypass Banner S9



Aksesoris tambahan pada LCIT RT5150
untuk bisa menampung kertas dgn panjang
s/d 1.260 mm dan berat s/d 216gsm
Kapasitas baki = 500 lembar
Berat = 30 kg


Extension Vacuum Feed Banner Sheet Tray Type S14

Aksesoris tambahan pada LCIT RT5150
untuk bisa menampung kertas dgn panjang
s/d 960 mm dan berat s/d 470 gsm
Kapasitas baki = 730 lembar
Berat = 9 kg



Booklet Finisher SR5120

Aksesoris keluaran kertas dan buku secara
otomatis dgn finishing Staples.
Maks. 30 lembar / 120 halaman per buku
Kapasitas penampung = 3.500 lembar
Ukuran kertas = 139,7 x 139,7 - 330 x 1.260mm
Berat = 160 kg



Staples Finisher SR5110

Aksesoris keluaran Staples pinggir, bisa
1 Staples diatas atau 2 staples dipinggir
secara otomatis
Maks. 100 lembar / 200 halaman per buku
Maks. Kertas = 40 - 470 gsm
Ukuran kertas = 139,7 x 139,7 - 330 x 1.260 mm
Berat = 135 kg

Multi Folding Unit FD5030

Aksesoris pelipat kertas.
Model Pelipatan = Half Fold, Z Fold,
Double Parallel Fold, dll
Ukuran kertas = 210 x 280 - 330 x 487 mm
Berat = 45 kg



EFI Fiery N-70A



Server EFI versi FS500 Pro yang
bermanfaat untuk mengontrol proses
cetak agar lebih terstruktur dan cepat.
Memiliki Fasilitas yang lebih lengkap.
CPU : Intel Xeon 4214 Silver
Memory : 32 GB
HDD : 480 GB SSD - OS
2 TB x 2 HDD SATA
Sistem Op : Win 10 IoT Enterprise 2019

EFI Fiery N-50A

Server EFI yang bermanfaat untuk
mengontrol proses cetak agar
lebih terstruktur dan cepat.
CPU : Intel i5 8500
Memory : 8 GB
HDD : 256 GB SSD - OS
1 TB HDD SATA
Sistem Op : Win 10 IoT Enterprise 2019



RICOH

RICOH Pro C7500

SYSTEM SPECIFICATIONS

Hardware Specifications

Process	4-drum (standard) / 5-drum (optional) dry electrostatic transfer system with internal transfer belt
Fusing	Oil-less, belt fusing method
Engine Speed	85 ppm (standard) 95 ppm (with the optional Productivity Upgrade Kit)
Max. Monthly Volume	240K
Duty Cycle	1,500K 1,700K (with the optional Productivity Upgrade Kit)
Resolution	2400 × 4800 dpi VCSEL
Warm-Up Time	Less than 300 sec.
Limitless Paper Supply	Supply Supported
Paper Size	13" × 19.2" – 13" × 49.6" (when using Oversize Tray option) 12.7" × 18.9" – 12.7" × 49.4" (when using the Oversize Tray option)
Maximum Printable Area	Tray 1: 52 – 300 gsm Tray 2: 52 – 256 gsm Trays 3 – 8: 40 – 470 gsm Optional Vacuum Feed LCIT RT5150
Paper Weight	Optional Bypass Tray 52 – 216 gsm Uncoated Paper, Coated Paper (gloss and matte), Recycled Paper, Preprinted, Letterhead, Pre-punched, Tab Stock, Textured Paper, Label Paper, Carbonless Paper
Paper Type	Tray 1: 1,000 sheets × 2 (Tandem) Tray 2: 500 sheets Tray 3 – 8: 2,200 sheets Optional Bypass Tray: 500 sheets Optional Banner Sheet Tray: 800 sheets Optional Extension Banner Sheet Tray: 500 sheets
Paper Capacity	Power Source Max. Power Consumption Typical Electricity Consumption (TEC)* 220 – 240 V, 16 A × 2, 50/60 Hz Less than 5,000 W 14,400,000 A4 pages or 5 years
ENERGY STAR	Certified
EPEAT	Silver (N-70A Controller)
Dimensions (W × D × H)	52" × 36" × 74" (including status pole)
Weight	Less than 1,235 lbs.

Printer Controllers

Fiery Controller N-70A/N-50A

Fiery System Version	Fiery FS500 Pro
Configuration	External
Memory	8GB RAM (4GB × 2)
CPU	i5-8500 Processor
HDD	SSD Boot Drive for OS and Fiery software + 1TB HDD
Operating System	Windows 10 IoT Enterprise 2019 LTSP

Accessories

Vacuum Feed Large Capacity Tray (LCIT RT5150)

(Max. 3 units per system)	
Paper Capacity	4,400 sheets (2,200 sheets × 2 Trays)
Paper Size	3.94" × 5.5" – 13" × 19.2"
Paper Weight	Trays 3 – 4: 40 – 470 gsm Trays 5 – 8: 40 – 400 gsm
Dimensions (W × D × H)	41.5" × 28.7" × 39.4"
Weight	507 lbs.

Vacuum Feed Oversize Tray Type S9

Paper Capacity	730 sheets
Paper Size	8.27" × 16.54" – 13" × 27.5"
Paper Weight	52 – 400 gsm Width of LCIT RT5120 will extend to 50.8"

Extension Vacuum Feed Banner Sheet Tray Type S14

Paper Capacity	500 sheets
Paper Size	8.27" × 16.54" – 13" × 38"
Paper Weight	52.3 – 470 gsm (16.54" – 19.2") 52.3 – 300 gsm (19.3" – 27.5") 63.1 – 300 gsm (27.6" – 38")

Multi Bypass Tray Unit (BY5020)

Paper Capacity	500 sheets
Paper Size	3.94" × 5.5" – 13" × 19.2" Maximum paper size extends up to 13" × 27.5" by adding the optional Multi Bypass Sheet Tray Type S9
Paper Weight	52 – 216 gsm

Cover Interposer Tray (CI5040)

Paper Capacity	400 sheets (200 sheets × 2 Trays)
Paper Size	5.5" × 8.5" – 13" × 19.2"
Paper Weight	52 – 350 gsm
Air Assist	Supported
Double Feed Detection	Optional
Dimensions (W × D × H)	13" × 28.7" × 50.8"
Weight	110 lbs.

4,500-Sheet Finisher with 100-Sheet Stapler (SR5110)

Paper Capacity	Lower Shift Tray: 3,500 sheets Upper Shift Tray: 1,000 sheets
Paper Weight	Lower Shift Tray: 52 – 470 gsm Upper Shift Tray: 52 – 350 gsm Optional 2/3 hole
Punch	39.2" × 28.7" × 55.7"
Dimensions (W × D × H)	298 lbs.
Weight	

3,500-Sheet Booklet Finisher with 100-Sheet Stapler (SR5120)

Paper Capacity	Lower Shift Tray: 2,500 sheets Upper Shift Tray: 1,000 sheets
Paper Weight	Lower Shift Tray: 52 – 470 gsm Upper Shift Tray: 52 – 350 gsm Optional 2/3 hole
Punch	7.2" × 10.2" – 13" × 19.2"
Saddle Stitch Staple	52 – 350 gsm
Paper Size	52 – 80 gsm up to 30 sheets/120 pages
Paper Weight	39.2" × 28.7" × 55.7"
Dimensions (W × D × H)	353 lbs.
Weight	

Booklet Trimmer (TR5050)

Trimming Type	One Side Edge
Trimming Capacity	Up to 30 sheets/120 pages
Paper Size	7.2" × 10.2" – 13" × 19.2"
Stack Capacity	Up to 60 sets
Limitless Stack	Supported
Dimensions (W × D × H)	43.9" × 23.3" × 21.9"
Weight	166 lbs.

High Capacity Stacker (SK5040)

Paper Capacity	5,000 sheets; Proof tray: Additional 250 sheets
Paper Weight	52 – 470 gsm
Rollaway Cart	Standard and Optional additional carts available
Dimensions (W × D × H)	35.4" × 28.7" × 39.8"
Weight	Stacker: 264 lbs.; Rollaway cart: 33 lbs.

FD5030 Multi-Folding Unit

Folding Type	
Single Sheet Mode	Z-Fold, Half-Fold/Print inside, Half-Fold/Print outside, Letter Fold-in/Print inside, Letter Fold-in/Print outside, Letter Fold-out
Multiple Sheets Mode	Half-Fold/Print inside, Half-Fold/Print outside, Letter Fold-in/Print inside, Letter Fold-in/Print outside, Letter Fold-out
Paper Size Single Sheet	Z folding: 8.5" × 11" – 12" × 18"; Half folding: 8.5" × 11" – 13" × 19.2"; Letter folding: 8.5" × 11" – 12" × 18"; Double Parallel folding: 8.5" × 11" – 12" × 18"; Gate folding: 8.5" × 11" – 12" × 18"
Multiple Sheets Mode	Half folding: 8.5" × 11" – 13" × 19.2"; Letter Fold-in: 8.5" × 11" – 12" × 18"; Letter Fold-out: 8.5" × 11" – 8.5" × 14"
Paper Weight	
Single Sheet Mode	64 – 105 gsm
Multiple Sheets Mode	64 – 80 gsm
Dimensions (W × D × H)	18.5" × 28.7" × 39.4"
Weight	203 lbs.

Plockmatic High Capacity Interposer (HCI3500)

Paper Capacity	3,500 sheets (1,750 sheets × 2 Trays)
Paper Weight	65 – 350 gsm
Paper Size	4.72" × 8.27" – 13" × 26"
Dimensions (W × D × H)	47.2" × 28.7" × 43"
Weight	551 lbs.

Plockmatic MPS – Oversize Sheet Stacker

Paper Capacity	2,000 sheets
Paper Weight	150 – 470 gsm
Paper Size	8.5" × 11" (LEF) – 13" × 49.6"
Dimensions (W × D × H)	35.4" × 26.8" × 41.8" (width extends to max. 55")
Weight	172 lbs.

Plockmatic Booklet Maker (PBM350e)

Paper Size	8.5" × 11" – 12" × 18"
Paper Weight	64 – 300 gsm
Set Size	2 – 35 sheets – 80 gsm
Dimensions (W × D × H)	55.9" × 35.4" × 27.6"
Weight	297 lbs.
Optional	Trim Module, Book Fold Module, Cover Feeder, Rotate, Crease Trimmer

Plockmatic Booklet Maker PBM5035/5035S

Paper Size	Staple: 8.11" × 8.27" – 12.6" × 24.4" Stitch: 4.27" × 8.27" – 12.6" × 24.4"
Paper Weight	18 lb. Bond to 130 lb. Cover (dependent on paper type and quality)
Book Thickness	Min. Set: 1 sheet of 20 lb. Bond Max. Finished Book: 0.393" (approx. 200 pages 20 lb. Bond) Max. Set: 0.137" or 0.196" (approx. 35 sheets and 50 sheets of 20 lb. Bond)

GBC StreamPunch Plus

Punched Paper Sizes	5.5" × 8.5", 8.5" × 11", 8.5" × 14", 11" × 17", 12" × 18"
Punched Media	75 – 300 gsm
Weight Range	
Tab Punching	Supported
"Two-Up" Punching	Supported
Dimensions (W × D × H)	17.5" × 28.7" × 39.4"
Weight	220 lbs.

GBC StreamWire (GBC StreamPunch Plus is required)

Paper Sizes	8.5" × 11" (LEF)
Paper Weight	75 – 300 gsm
Number of Loops	8.5" × 11" (LEF) – 32 loops
StreamWire Supply	Black, White or Silver Up to 30, 50, 60, 70 or 80 Sheets
Tab Stock	Supported
Dimensions (W × D × H)	34" × 38" × 34"
Weight	500 lbs.

Additional Accessories

Multi Bypass Banner Sheet Tray Type S9, Buffer Pass Unit Type S9, Bridge Unit BU5020, Extension Output Banner Sheet Tray Type S14, SR5000 Series Output Tray for Banner Sheet Type S6, Perfect Binder GB5010, Plockmatic LCT3500 XL, Plockmatic CT XL, RPIP Interface Box Type S3

Consumables

Black Toner	67.0K prints/bottle*
Cyan Toner	67.0K prints/bottle*
Magenta Toner	67.0K prints/bottle*
Yellow Toner	67.0K prints/bottle*
Clear Toner	29.2K prints/bottle**
White Toner	19.0K prints/bottle**
Neon Yellow Toner	27.8K prints/bottle**
Neon Pink Toner	27.8K prints/bottle**
Invisible Red Toner	20.6K prints/bottle**
Silver Toner	19.0K prints/bottle**
Gold Toner	19.0K prints/bottle**
Waste Toner Bottle Yield	175K prints/bottle*

*Based on 8.75% coverage (LT)

**Based on 15% coverage (LT)

TCRU Program	Supported
--------------	-----------

Workflow Solutions Supported

RICOH ProcessDirector®, RICOH TotalFlow™ Producer, RICOH TotalFlow Prep, RICOH TotalFlow Production Manager, RICOH TotalFlow BatchBuilder™, EFI DirectSmile, ePS MarketDirect StoreFront, CGS/ORIS Lynx & Evaluate Fiery® Central, Fiery Color Profiler Suite, Objectif Lune

Specifications are subject to change without notice.
Contact Ricoh for a list of certified media.



EPEAT Silver rating is applicable only in the USA.

Exclusive Distributor :



PT. SETIAWAN SEDJATI

Mugi Griya Building 8th Floor
Jl. M.T. Haryono Kav.10
Jakarta 12810, Indonesia
Telp. : (021) 8308521 - 27
Fax. : (021) 8308529
www.setiawansedjati.com

Branch Office & Stations :

* Medan * Banda Aceh * Lhokseumawe * Pematang Siantar * Padang * Pekanbaru * Palembang
* Jambi * Bandar Lampung * Pangkal Pinang * Jakarta 1 * Jakarta 2 * Jakarta 3 * Banten * Bogor
* Bekasi * Bandung * Cirebon * Tasikmalaya * Sukabumi * Karawang * Semarang * Tegal
* Pekalongan * Yogyakarta * Solo * Purwokerto * Magelang * Surabaya * Malang * Jember
* Banjarmasin * Balikpapan * Pontianak * Denpasar * Mataram * Kupang * Maumere * Makassar
* Manado * Palu * Palopo * Kendari * Sorong * Ambon * Manokwari * Jayapura * Merauke